



CONFINED SPACE

Tripod

TRIPOD

The BTS Pro-3 Series 3 stage 3m lightweight aluminium tripod offers workers a practical and user friendly solution for safe means of access & egress including rescue/recovery in vertical confined space applications.



TRIPOD				
Model Description	Maximum Height m (ft)	Collapsed Height m (ft)	Weight kg (lbs)	Code
PRO-3, 3m 3 stage	3.02 (9.90)	1.55 (5.08)	19.8 (43.65)	40014

PRO-SERIES TRIPOD ACCESSORIES	
Model Description	Code
Tripod Storage bag c/w wheels	30014SCB
Quick Release Double Sided Universal Male Interface Bracket.	60202UAT
Female Single Pro-Series Universal Interface Davit Winch Bracket.	60202UF
Tripod Top Pully Assembly.	30173
IKAR PRO-Series Davit Bracket c/w Female Single Interface Brackets.	60202UIM
Quick Release Male Tripod Bracket (Toolless).	30014SB
BTECH Man / Materials Rated Winch with 18, 30, 45, 60, 76 & 90m (59, 98, 147, 196, 249 & 295 ft) wire rope.	See page 42-43
S/S Material Winch c/w Female Interface Bracket with 18m x 6mm (59' x 1/4") HDG W/R with G80 Swivel S/L Hook.	SSJC-C820
S/S Material Winch c/w Female Interface Bracket with 18m x 6mm (59' x 1/4") S/S W/R with G100 Swivel S/L Hook	SSJC-C820S
IKAR Recovery Winch 12, 18 or 24 m (39, 59 or 78 ft).	HRA-12TA, HRA-18TA HRA-24TA
Diversion Sheave Block with S/S Karabiner .	41-Z20
Spreader Bar.	BRO5110

PRODUCT FEATURES

- Individually adjustable telescopic legs with toe spikes, bolt/peg holes and chain holes for added stability.
- BTS-Klick dual action quick release buttons for fast and reliable height adjustment.
- Lightweight aluminium construction.
- Tripod head features integrated pulley wheel allowing for winch wire cable to pass through centre of Tripod.
- **Additional rated 3 tie-off points in the Tripod head for attaching additional personal fall protection equipment.**
- Powder coated in Hi-Vis Safety Orange for ease of identification in all work areas.
- Compatible for use with other reputable height safety manufacturer's winches.
- Tripod comes complete in canvas storage bag with wheels for ease of storage and transport by one person.
- Minimal set up required - Assembled by one person.
- Use of chain optional.

Weight:	19.8 kg (43.65 lbs)
Maximum Height:	3.02 m (9.90 ft)
Minimum Height:	1.55 m (5.08 ft)
Capacity:	Max. 2 users, 1 person no more than 140kg (310 lbs) per anchor point
Rated:	12kN (2,700 lbs) per anchor point

