

ANCHOR-TO-GO

TEMPORARY SHEET METAL ROOF ANCHOR

AAP000M



A Simple and effective primary anchor for access onto sheet metal roofs, the ZERO® Anchor-to-Go has interlocking cam clamps to secure the anchor to the edge of the roof sheeting (in the gutter line). This fast setup makes the Anchor-to-Go perfect for plumbers, painters, service technicians and installer that require short term roof access.

By attaching a rope line to the anchor with a snap hook or carabiner and placing it over the ridgeline, access can be made from the opposite side of the roof allowing secondary diversionary anchors to be installed.

RATING: 15kN

LIFESPAN: Up to 10 Years

CERTIFICATION:

Complies with AS/NZS 1891.4:3.2007

AS/NZS 1891.4:3:2007 Anchorages, (a)Single point anchorages - Limited free fall-arrest, Restraint technique



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
AAP000M		3700g	49 x 50cm	Powder coated steel	15kN

PRODUCT FEATURES

- Rated for one person (15kN).
- Does not require any fixings.
- 0.42mm minimum roof thickness.
- Steel construction.
- 2x Cam clamp fixing points.
- Non-scratch cap.
- Fall arrest and work restraint use.
- For temporary use only.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
 10 Holt Place, Harewood,
 Christchurch 8053, New Zealand
 sales.nz@zeroheightsafety.com

EUROPE & UK
 Badenerstrasse 122,
 5466 Kaiserstuhl, Switzerland
 sales.eu@zeroheightsafety.com

